



SIROMER Equipment

Your Tractor's Best Friend

HAY RAKE



Ideal for rowing up before bailing fully will also spread freshly mown grass to aid with fast drying

As a tedder:

- 1). Spread, swath or windrow so crops dry down faster,
- 2). Tailor your tedding operations to a variety of crops and conditions by varying PTO speed or tine position,
- 3). Fixed-tine position provides aggressive tedding and is ideal for use in fresh-cut material or crops where leaf and shatter losses are not a concern
- 4). Cam-operated tine position allows the tine bar rollers to follow the cam track to lift and release crop gently to save valuable leaves

As a rake:

- 1). Precise raking action produces fluffy, uniform windrows that dry evenly
- 2). Self-centring wheels provide extra manoeuvrability by allowing you to make sharp turns and back up easily without lifting the machine.

Strong, rugged frame provides years of dependable performance.

Three wheel-height position let you adjust for different crops, conditions and operations.

Vertical tines pick up fewer stones and less debris than horizontal tines for cleaner tedding and raking.

Convenient jack simplifies three-point hitch arrangements.

Tedding width	250cm
Weight	160kg
Tines per rotor	4
Numbers of rotors	6
Working speed	4-8km/h
Power required	20-40hp

Tel: 01253 799 029
Fax: 01253 790 006
Web: www.siromer.co.uk

Specification subject to change without notice.
Information is for guidance only.